



X⁴ 7300



**EXCEPTIONAL TEMPERATURE CONTROL
WITH A NEW DIMENSION IN
PERFORMANCE AND EFFICIENCY.**



Condenser Dimensions

76.4" x 85.7" x 22.8"
(1,940 x 2,176 x 579 mm)

Evaporator Dimensions

66.3" x 45.2" x 8.2"
(1,684 x 1,149 x 280 mm)

Body Opening

66.8" x 46.0"
(1,696 x 1,168 mm)

Approximate Weight

1,685 lb. (765 kg)
Remote 50 gallon aluminum fuel tank with
mounting brackets: 65 lb. (29 kg)
Battery: 50 lb. (23 kg)

Cooling/Temperature Capacity

Ambient at 100°F (38°C)

Evaporator Return Air Temp.	High Speed Diesel Operation	
	BTU/hr	Watts
35°F (2°C)	66,000	19,345
0°F (-18°C)	35,000	10,260
-20°F (-29°C)	23,000	6,740

Evaporator Airflow:

Applied system performance:
3,050 cfm (5,180 m³/hr)

The X4™ Series. Built upon the proven X2™ platform, the X4 7300 unit sets the bar even higher as the new industry standard for refrigeration performance and efficiency.

Ultra high capacity. The model 7300 establishes the benchmark for extreme performance. It delivers fast pull-down, precise temperature control and peace of mind for the most demanding applications.

Ultra high efficiency. EcoFORWARD™ technologies deliver significant fuel savings as well as higher performance, lower operating costs and compliance with 2013 EPA emissions regulations.

Proven reliability. The enhanced platform now includes proven high efficiency components from our Vector™ series and an industry-leading warranty for dependability and peace of mind.

APX™ control system. The modular APX system combines remarkable control intelligence, temperature control and system reliability with amazingly simple operation.

Lower cost of ownership. Combining innovative engineering with a straightforward, practical design means less fuel consumption, reduced engine run hours, and lower maintenance costs.

Standard Features Include:

- Tier 4 Final V2203L smart diesel engine
- 4 cylinder 2.2 liter direct injection
- 24.8 hp (18.5kW) at 1,800 RPM high speed
- CAN bus electronic interface
- 15 qt. (14.2 liter) oil capacity
- High power 70 amp alternator
- ESI™ (Extended Service Interval) package
- 3,000 hour service interval
- Multistage, synthetic media oil filter
- Water separating fuel filter
- Heavy duty, low noise dry air cleaner
- Extended life coolant
- 05G 41CFM compressor
- 40 in³ displacement
- 6 cylinders
- Refrigerant R-404A, 16.0 lb (7.3 kg)
- UltraFresh 3™ temperature control
- TRU-DEMAND™ high energy efficiency
- Electronic expansion valve
- Electronic suction modulation
- Compressor unloaders
- Brazed plate heat exchanger
- Automatic start/stop fuel saver
- Automatic hot gas heating system
- APX™ Control System
- IntelliSet™ with ProductShield™
- DataLink™ data recorder
- Information dashboard
- Multilingual graphical display
- Pretrip and Virtual Tech diagnostics
- Integrated USB port

Standard Features (continued):

- High efficiency microchannel condenser
- Vortex Suppression Fan
- Condenser coil hail/bug guard
- TurboAir™ evaporator management
- Composite doors with single release latch
- Installation package
- Screw post battery terminals
- Remote aluminum fuel tank
- 50 gal. single fill, 22"
- Remote light bar
- Full bottom panel

Accessories and Options:

- eSolutions™ telematics system for remote monitoring and control
- DataTrak™ remote communications
- Open trailer door indicator and shutdown switches
- Fuel heater
- Evaporator drain line extensions
- APX Remote Control Panel
- Premium ECR hoses
- Remote temperature probes
- Stealth™ 2 noise reduction package
- Unit impact protection bumpers
- High power 105 amp alternator
- Extra heavy duty suction side fuel filter
- Fuel tank level and shutdown sensor
- Chrome grille/stainless latch package
- Refrigerant R-452A, 16.0lb (7.3kg)
- Custom color paint
- AutoFresh™ air exchange
- Remote aluminum fuel tanks:
 - 30 gal. or 75 gal. single fill, 22"
 - 100 gal. single or double fill, 22"
 - 120 gal. single or double fill, 22"

APX™
CONTROL SYSTEM

Specifications are subject to change without notice.
Warranty: Product warranty and limitations are outlined in Form 62-11669.
This warranty is applicable only in North America. Consult your Carrier Transicold representative for warranty coverage elsewhere. Form 62-11663 Rev H.

North America
Carrier Transicold
700 Olympic Drive
Athens, GA 30601 USA

Central America and Mexico
Carrier Transicold
Ejercito Nacional 253-A Piso 5
Colonia Anahuac
11320 Mexico D.F.

